



Item Number	Base Option	Capacity	Range
930+2089+000	System Clamp / Grommet / Drilling Screw	18 lbs	20.28"
930+2159+000	System Clamp / Grommet / Drilling Screw	33 lbs	20.28"
980+2089+000	TSS Column Mount	18 lbs	21.54"
980+2159+000	TSS Column Mount	33 lbs	21.54"
981+2089+000	SlatWall	18 lbs	21.65"
931+2089+000	Wall Mount	18 lbs	21.65"

A comfortable ergonomic viewing position for computer monitors is essential for preventing eye and neck strain. LiftTEC® Arms move smoothly and stay in place with one-handed operation, providing easy adjustments for a perfect personal fit.

The LiftTEC® Arm II is a two-part monitor arm with a range of 20.28" and a maximum height of 16" above the desk surface. Available in two capacities, the Arm II can hold a monitor weighing up to 18 or 33 lbs. Gas-Spring Technology makes it easy to position the monitor and keep it in place.

The entire arm can be rotated 360° around it's table mount for easily sharing your view. It provides a clean, modern style to suit any work environment.

3-in-1 table mount options are included with the Arm II - Drilling Screw, Grommet, and System Clamp. Models are also available for TSS column mount. SlatWall mount, or a Wall Mount.

The Arm II is equipped with a QuickRelease mount - simply click the monitor in place and tilt to the perfect viewing angle. Cable clips are included to maintain a neat, organized appearance.

FEATURES

- Adjustability: tilt/turn angle, height, range, rota-
- Range: 20.28" to 21.65"
- Carrying capacity: up to 18 or 33 lbs
- Maximum height of monitor arm from desk surface: 16"
- Pivot: 360 degree pivot on table mounts; 180 degrees on column, slat, and wall mounts
- Gas Spring Technology piston for smooth, easy positioning
- Die cast aluminum construction for superior strength
- German engineered for quality
- Mounting standard: VESA 75/100

HIGHLIGHTS









Certification



BASE OPTIONS













Dahle North America, Inc. 49 Vose Farm Road Peterborough, NH 03458 (800) 995.1379 www.NovusMoreSpace.com

