

Projector Wall Mount - Universal - Short Throw

Product ID: PROJWALLMNT



The adjustable mount for short throw projectors helps you create a large image from a short distance and keeps your projector out of the way. It's ideal for classrooms, boardrooms, hospitality venues, and many other meeting spaces.

Supporting a wide range of projector brands, the short throw projector wall mount features a universal mounting pattern of 12.8" (325 mm) diameter and supports a weight capacity of 33.3 lb. (15 kg).

Adjust the distance of your projector from the wall using the telescopic arm, which extends from 16.5" to 27.7" (420 mm to 705 mm). The arm on the low-profile projector wall mount also tilts ± 5 degrees to help you find the ideal position. The lockable ball joint on the adjustable projector mount provides 360-degree swivel, ± 25 degree horizontal / vertical tilt.

StarTech.com conducts thorough compatibility and performance testing on all our products to ensure we are meeting or exceeding industry standards and providing high-quality products to IT Professionals. Our local StarTech.com Technical Advisors have broad product expertise and work directly with our StarTech.com Engineers to provide support for our customers both pre and post-sales.

PROJWALLMNT is backed by a StarTech.com 2-year warranty and free, lifetime technical support

Certifications, Reports and Compatibility



Applications

- Mount a short throw projector in classrooms, lecture halls, or hospitality venues
- Ideal for boardrooms, lobbies, meeting rooms or other business applications

Features

- Sturdy mount supports a wide array of short-throw projectors with a universal mounting pattern of 12.8" (325 mm) diameter
- Telescopic arm extends 16.5" to 27.7" (420 mm to 705 mm) from the wall and supports a weight capacity of 33.3 lb. (15 kg)
- Optimum viewing with a lockable ball joint providing 360 degree swivel and +/- 25 degree horizontal/vertical tilt
- Steel and aluminum mount features built-in cable management

Performance	Warranty	2 Years
	General Specifications	Supports Short-Throw Ratio: 0.4:1
	General Specifications	Universal Mounting Pattern: 325 mm Diameter (12.8")
	General Specifications	Weight Capacity: 15kg (33.1 lb.)
	General Specifications	Wall Mount Arm Tilt: +/- 5
	General Specifications	Lockable Ball Joint: 360 Swivel, +/- 25 Horizontal & Vertical Tilt
	Minimum Arm Extension	16.5 in [4.2 cm]
	Maximum Arm Extension	27.8 in [7.0 cm]
Environmental	Operating Temperature	0C to 40C (32F to 104F)
	Storage Temperature	-20C to 60C (-4F to 140F)
	Humidity	40~60% RH
Physical Characteristics	Material	Steel, Aluminum and Plastic
	Product Length	28.9 in [7.4 cm]
	Product Width	7.1 in [1.8 cm]
	Product Height	7.7 in [2.0 cm]
	Weight of Product	7.5 lb [3.4 kg]
Packaging Information	Package Length	22.4 in [5.7 cm]
	Package Width	11.2 in [2.8 cm]
	Package Height	5.7 in [1.4 cm]
	Shipping (Package) Weight	9.7 lb [4.4 kg]
What's in the Box	Included in Package	Wall Bracket
	Included in Package	Projector Pole
	Included in Package	Upper, Decorative Wall Cover

Included in Package	Lower, Decorative Wall Cover
Included in Package	Adjustment Module
Included in Package	Right, Adjustment Module Cover
Included in Package	Left, Adjustment Module Cover
Included in Package	Pole End Cap
Included in Package	Wall Anchors
Included in Package	M3 x 24 mm Screws
Included in Package	M4 x 24 mm Screws
Included in Package	M5 x 24 mm Screws
Included in Package	M6 x 24 mm Screws
Included in Package	M6 x 8 mm Hex Screws
Included in Package	M6 x 25 mm Hex Screw
Included in Package	Nuts
Included in Package	User Manual
Included in Package	M6 x 10 mm Screws
Included in Package	Wrench (10mm)
Included in Package	Mounting Screws
Included in Package	Washers
Included in Package	Mounting Arm Covers
Included in Package	Hinge Connector
Included in Package	5 mm Hex Key
Included in Package	Mounting Arms

****Product appearance and specifications are subject to change without notice.***

