Key **Features**

- 100% sRGB and 100% Rec.709 colour coverage
- USB-C connectivity with 90W power delivery
- Certification validated by Pantone
- 4K Ultra HD resolution
- World 1st TÜV SÜD tested color blindness mode



Product **Description**

Designed to deliver unmatched color accuracy crucial for professional applications, the ViewSonic ColorPro® VP2768a-4K UHD monitor displays your work with the vivid and lifelike color it deserves. With Pantone validated 100% sRGB color coverage, this monitor provides industry standard color to ensure accurate results. Enjoy reliable and flexible network connectivity with the integrated gigabit Ethernet port while the USB-C provides single cable solution for connecting and charging all peripherals and accessories. In addition to the future proof connectivity with USB3.2 Gen 1 HDMI, DisplayPort (DP) allows you to daisy chain monitors from USB-C or DP out ports for multi-monitor setups. To ensure precise, uniform color, each of our monitors is factory calibrated to deliver an amazing Delta E < 2 value for superior color accuracy. An integrated color uniformity function ensures consistent chromaticity across the screen, while a 14-bit 3D look-up table generates a stunningly smooth palette of 4.39 trillion colors. What's more, an advanced ergonomic design delivers customized comfort for increased productivity. Hardware calibration function is also available which allows you to quickly and easily calibrate the monitor for photography, graphic design, content creation, and other color-critical applications.



| DISPLAY | | CONNECTOR | | WEIGHT (IMPERIAL) | |
|------------------------------|--|-----------------------------|---|-------------------------------|---|
| Display Size (in.): | 27 | USB 3.2 Type A Down Stream: | 2 | Net (Ibs): | 14.7 |
| Viewable Area (in.): | 27 | USB 3.2 Type B Up Stream: | 1 | Net Without Stand (lbs): | 9.6 |
| Panel Type: | IPS Technology | USB 3.2 Type C Up Stream; | 1 | Gross (Ibs): | 21.8 |
| Resolution: | 3840 x 2160 | DisplayPort Alt mode : | | WEIGHT (METRIC) | |
| Resolution Type: | UHD | 3.5mm Audio Out: | 1 | Net (kg): | 6.7 |
| Static Contrast Ratio: | 1,300:1 (typ) | HDMI 2.0 (with HDCP 2.2): | 2 | Net Without Stand (kg): | 4.4 |
| Dynamic Contrast Ratio: | 20M:1 | DisplayPort: | 1 | Gross (kg): | 9.9 |
| Light Source: | LED | Power in: | 3-pin Socket (IEC C14 / CEE22) | DIMENSIONS (IMPERIAL) (WXHXD) | |
| Brightness: | 350 cd/m² (typ) | Ethernet LAN (RJ45): | 1 | Packaging (in.): | 29.1 x 16.4 x 8.7 |
| Colors: | 1.07B | POWER | | Physical (in.): | 24.1 x 16.26~21.38 x 8.5 |
| Color Space Support: | 10 bit (8 bit + A-FRC) | Eco Mode (Conserve): | 25.5W | Physical Without Stand (in.): | 24.1 x 13.9 x 2 |
| Aspect Ratio: | 16:9 | Eco Mode (optimized): | 30.1W | DIMENSIONS (METRIC) (WXHXD) | |
| Response Time (Typical GTG): | | Consumption (typical): | 39.1W | Packaging (mm): | 740 x 417 x 220 |
| Response Time (GTG w/OD): | 5.9 ms | Consumption (max): | 44.9W | Physical (mm): | 613 x 413.02~543.02 x 215 |
| Viewing Angles: | 178° horizontal, 178° vertical | Voltage: | AC 100-240V, 50/60 Hz | Physical Without Stand (mm): | 613 x 353 x 50 |
| | | Stand-by: | 0.5W | GENERAL | |
| Backlight Life (Hours): | 30000 Hrs (Min) | Power Supply: | Internal | | cTUVus, FCC-B, ICES003, Energy Star 8.0, EPEAT Silver, CEC, NOM, Mexico Energy, CE, CE EMC, CB, RoHS, ErP, REACH, WEEE, EAC, UkrSEPRO, UKCA, CCC, China RoHS, China Energy Label |
| Curvature: | Flat | ADDITIONAL HARDWARE | | Regulations: | |
| Refresh Rate (Hz): | 60 | Kensington Lock Slot: | 1 | regulations. | |
| Blue Light Filter: | Yes | Cable Organization: | Yes | | |
| Flicker-Free: | Yes | CONTROLS | | | VP2768A-4K x1, 3-pin Plug (IEC C13 / CEE22) x1, HDMI Cable |
| Color Gamut: | EBU: 108% size / 99% coverage (Typ)REC709: 109% size / 100% coverage (Typ)SMPTE-C: 118% size / 100% coverage (Typ)NTSC: 78% size (Typ)sRGB: 109% size / 100% coverage (Typ) | Physical Controls: | Key 1, Key 2, Key 3, Key 4, Key 5, Key 6 (power) | PACKAGE CONTENTS: | (v2.0; Male-Male) x1, USB Type-C Cable (Male-Male) x1, USB A/B |
| | | On Screen Display: | Input Select, Audio Adjust, ViewMode, Color Adjust, Manual Image Adjust, Setup Menu | | Cable (v3.2; Male-Male) x1, Quick Start Guide x1 Please dispose of in accordance |
| Pixel Size: | 0.155 mm (H) x 0.155 mm (V) | OPERATING CONDITIONS | | Recycle/Disposal: | with local, state or federal laws. |
| Surface Treatment: | Anti-Glare, Hard Coating (3H) | Temperature: | 32°F to 104°F (0°C to 40°C) | Warranty: | *Warranty offered may differ from market to market |
| COMPATIBILITY | | Humidity (non-condensing): | 20% to 90% | Power Management: | Energy Star standards, EPEAT |
| PC Resolution (max): | 3840x2160 | WALL MOUNT | | Total Management | Energy of an standards, En Est |
| Mac® Resolution (max): | 3840x2160 | VESA Compatible: | 100 x 100 mm | | |
| PC Operating System: | Windows 10 certified; macOS | INPUT SIGNAL | | | |
| | compatible | Frequency Horizontal: | 15 ~ 136KHz | | |
| Mac® Resolution (min): | 3840x2160 | Frequency Vertical: | 24 ~ 75Hz | | |

Type C

130

120°

-5° / 21°

90°/90°

TMDS - HDMI (v2.0), PCI-E -DisplayPort (v1.4), Micro-Packet -

VIDEO INPUT

Digital Sync:

ERGONOMICS

Swivel:

Height Adjust (mm):

Tilt (Forward/Back):

Pivot (Right/Left):